



Specifically designed for the high speed progressive stamping of Terminals, Connectors and Switchgear Parts

Specs / Model	VHS 25	VHS 35	VHS 50
Capacity, Tf	25	35	50
Stroke, mm	30		
Speed, Variable, spm	200-800		200-600
Rated Tonnae point, mm before BDC	1.2		1.6
Slide Size, mm LR x FB	350 x 250	400 x 300	500 x 350
Die Height, SDAU, mm	210	235	250
Slide Adjustment, mm	30		
Bolster Size, mm LR x FB	600 x 330	700 x 380	800 x 450
Main Motor, Inverter, kW	5.6	7.5	11.25

Standard Features:

Certified JIS B 6402 Grade "Special" Accuracy | Cast Frame for high stability and low vibrations | Inverter Drive | Dynamic counterbalance | Slide Cushion | Rotary Cam limit switch | Crank angle Indicator | Die height Indicator | Pre-set Counter | Magnetic Stroke Counter | Automatic Oil Lubrication system | Anti-Vibration mounting Cushion | Mis-feed signal Input | Tool Box | Operation and Service Manuals in English / Chinese

Taiwan Quality | Local Support | 1 year Warranty | Integration options Direct-to-User Prices





Model / Price USD	VHS 25	VHS 35	VHS 50
Base Model with Standard Features	US\$36,000	US\$43,000	US\$60,000
High speed Gripper Feeder with direct drive	US\$15,000 (Max. 1.5 x 60mm width)		US\$ 22,000 (Max. 1.5 x 120mm width)
2 Channel BDC Monitor with Sensors	US\$2,000		
Horizontal Multi-Stack Pallet Un-Coiler	US\$ 3,000 (Max. 8	5mm / 1000 Kgs)	US\$ 3,300 (Max. 100mm / 2000 Kgs)

Terms: FCA, Taichung, Taiwan. 15% advance with Order, balance by LC/TT before shipment. 1 year manufacturing-defect warranty. Delivery: 90 days. Local services extra. Limited validity, ask for Quotation. Specs subject to change.

www.unipress.com.tw

UNIPRESS



UNITECH METALFORMING TECHNOLOGIES TAIWAN CO. LTD.

No.473, Sec. 1, Dongxing Rd., Nantun Dist., Taichung City 40854, Taiwan | Tel: +886-4-2471-3400, +886-4-2471-3800 Fax: +886-4-2471-4000

email: sales@unipress.com.tw